

Remote Control Wall Fan

KC-4GR 40cm/16"



- Remote control with 3 preset speed
- 1-6 hours timer
- Manual on/off and oscillation control
- Soft touch control panel

Wall Fans

KU308 30cm/12"
 KU408 40cm/16"
 KU408 YG 40cm/16"
 KU453 45cm/18"



- 3-speed On/Off pull switch
- Oscillation Control by pull switch
- Flexible neck adjustment

KV408 40cm/16"



- 3-speed On/Off pull switch
- Oscillation Control by pull switch
- Flexible neck adjustment
- Metal blade

Industrial Wall Fan

K50RA 50cm/20"



- 3-speed and off by push button switch
- Oscillation control
- Safety mesh wire guard

Commercial Wall Fan

KU50Y 50cm/20"



- 3 speed ON/OFF pull switch
- Full automatic oscillation
- Aluminium blade for stronger airflow and durability
- Turbo Fin Guard design generates airflow up to 10 meter distance
- New Front Guard Locking System
- Added angle adjust bolt for extra stability

Ceiling Mounted Ventilating Fans

15TGQZ 15cm/6"
 20CQT1 20cm/8"
 25TGQ7 25cm/10"



- Q-blade design
- High efficiency airflow
- Durable and long lasting operation
- Low noise and energy saving

Ceiling Mounted Sirocco Ventilating Fans

24JRB Smarto



- Motion sensor
- DC Motor Technology
- Variable speed selection
- Low Noise with Resonance Absorption Structure
- Taper blade design for high performance
- 15 minute delay timer

17CUF 24CUF



- Low Noise with Resonance Absorption Structure
- Taper blade design for high performance
- Ball bearing type motor for durability
- Reverse flow prevention shutter

17CFM 24CFM



- Low Noise with Resonance Absorption Structure
- Taper blade design for high performance
- Ball bearing type motor for durability
- Reverse flow prevention shutter

Glass Mounted Ventilating Fans

15WUD 15cm/6"
 20WUD 20cm/8"



- Advanced blade design
- Ball bearing condenser motor
- Pull cord operated shutter
- Fit window panel thickness 3mm to 7mm
- Low noise
- Suitable for bathrooms

Wall Mounted Ventilating Fans

En縁 10EGKA 10cm/4"
 Zen禅 15EGKA 15cm/6"
 EZ Fans



- Excellent for bathroom
- Easy installation
- Equipped with full accessories
- Easy Cleaning
- Energy saving
- Exhaust moisture and odour, preventing mould

25AUFA 25cm/10"
 Raku-Raku



- Advanced blade design
- High exhaust performance
- Aluminium punching filter with non-stick coating
- Oil container with collected oil level indicator
- Suitable for kitchen use

Wall Mounted Ventilating Fans

15AAQ1 15cm/6"
 20AQM8 20cm/8"
 25AQM7 25cm/10"
 30AQM8 30cm/12"



- Q-blade design
- High efficiency airflow
- Durable and long lasting operation
- Low noise and energy saving
- Automatic shutter

20ALH 20cm/8"
 25ALH 25cm/10"



- Curve shape front louver design
- Aerodynamic blade design
- High efficiency airflow
- Ball bearing type motor for durability
- Low noise and energy saving
- Automatic shutter

30KQT 30cm/12"
 40KQT 40cm/16"
 50AEQ2 50cm/20"



- Large metal blade assembly for abundant air volume
- Powerful, efficient and durable condenser motor
- Possible to install horizontally
- Automatic shutter
- Ideal for factories, warehouse, restaurant, workshop

Toxic pollutants can be absorbed into our body in many ways. Fumes and chemicals emissions during cooking can poison us through the air we breathe. Install Ventilating Fans in the kitchen to enable adequate air exchange and prevent poisonous pollutions of the air in the kitchen.

Specifications

| Model | RPM | | Capacity (CFM) | Wattage | | Noise Level (dB) | Operating Weight (kg) |
|-------------------|-----------|-----------|----------------|-------------|-----------|------------------|-----------------------|
| | Low | High | | Low | High | | |
| K11Z1 | 124 | 257 | 6004 | 21.0 | 58.0 | 49.5 | 5.10 |
| K14X2 / K14X2-PBR | 113 | 257 | 7416 | 33.5 | 65.0 | 51.0 | 5.10 |
| K14XZ | 102 | 196 | 7593 | 20.0 | 68.0 | 51.0 | 7.00 |
| K14YZ | 95 | 183 | 7593 | 21.0 | 69.0 | 51.0 | 7.60 |
| K14Y2 | 102 | 215 | 7946 | 19.5 | 85.0 | 52.0 | 6.20 |
| K15Y2 | 84 | 195 | 7946 | 20.5 | 85.0 | 48.0 | 7.40 |
| K14ZW | 81 | 239 | 7946 | 2.5 | 41.0 | 51.0 | 4.90 |
| K15Z5-QEY/ REY | 80 | 235 | 8652 | 3.0 | 41.0 | 54.0 | 5.10 / 5.30 |
| K15YX-RBR/ SBR | 80 | 235 | 8652 | 3.0 | 41.0 | 54.0 | 5.10 / 5.30 |
| K12UX | 80 | 236 | 6603 | 3.0 | 46.0 | 50.0 | 4.90 |
| K15UW / K15UW-QEY | 80 | 235 | 8652 | 3.0 | 63.0 | 53.0 | 6.20 |
| K12V0 / K12V0-PBR | 131-177 | 273-333 | 5721 | 15.1-20.5 | 47.7-58.3 | <58 | 4.60 |
| K12W0 | 131-177 | 273-333 | 5721 | 15.1-20.5 | 47.7-58.3 | <58 | 4.80 |
| K15V0/K15V0-PBR | 81-118 | 216-264 | 8122 | 14.7-19.9 | 67.5-82.5 | <62 | 5.10 |
| K15W0 / SL | 81-118 | 216-264 | 8122 | 14.7-19.9 | 67.5-82.5 | <62 | 5.30 |
| K15W0-S | 81-118 | 216-264 | 8122 | 14.7-19.9 | 67.5-82.5 | <62 | 5.30 |
| K18NY-RBR/SBR | 80 | 185 | 11,477 | 6.0 | 55.0 | 54.0 | 11.70/11.90 |
| KB-304 | 878-1074 | 1123-1373 | 1518 | 25.2-30.8 | 34.7-42.5 | <47 | 3.20 |
| KB-404 | 774-946 | 1103-1349 | 2225 | 38.9-47.5 | 49.9-60.9 | <60 | 4.30 |
| KX-405 | 765-935 | 1089-1331 | 2225 | 40.8-49.8 | 52.2-63.8 | <60 | 8.30 |
| KC-4GR | 774-946 | 1103-1349 | 2225 | 43.0-52.7 | 53.4-65.2 | <60 | 4.60 |
| KU453 | 730-892 | 961-1175 | 3355 | 41.6-50.8 | 54.2-66.3 | <60 | 5.00 |
| KU308 | 871-1065 | 1158-1416 | 1589 | 30.0-36.6 | 39.8-48.6 | <50 | 3.30 |
| KU408 / YG | 774-946 | 1103-1349 | 2225 | 38.9-47.5 | 49.9-60.9 | <60 | 4.45 |
| KU50Y | 940 | 1280 | 3884 | 60.0 | 70.0 | 59.0 | 6.00 |
| K50RA | 1082-1346 | | 6710 | 105.0-146.0 | | 62.0 | 13.10 |
| 15TGQZ | 1330 | | 141 | 12 | | 35.0 | 1.20 |
| 20CQT1 | 1207 | | 265 | 25.7 | | 41.0 | 1.80 |
| 25TGQ7 | 959-1172 | | 367 | 24.8-30.3 | | 45.0 | 1.90 |
| 24JRB | 794 | | 94 | 8.0 | | 31.0 | 2.90 |
| 17CUF | 790 | | 50 | 11.0 | | 26.0 | 1.90 |
| 24CUF | 690 | | 82 | 14.0 | | 28.0 | 2.90 |
| 17CFM | 900 | | 53 | 13.0 | | 29.0 | 2.00 |
| 24CFM | 790 | | 94 | 17.0 | | 31.0 | 3.20 |
| 15WUD | 1463 | | 124 | 8.0 | | 35.0 | 0.90 |
| 20WUD | 1042 | | 212 | 16.0 | | 32.0 | 1.10 |
| 10EGKA | 2732 | | 45 | 6.4 | | 33.0 | 1.20 |
| 15EGKA | 2405 | | 96 | 6.9 | | 35.0 | 1.50 |
| 25AUFA | 1100 | | 491 | 34.0 | | 42.0 | 2.80 |
| 15AAQ1 | 1480 | | 170 | 15.0 | | 31.0 | 1.40 |
| 20AQM8 | 1109-1301 | | 318 | 14.9-18.3 | | 37.0 | 2.30 |
| 25AQM7 | 999-1221 | | 530 | 25.2-30.8 | | 39.0 | 2.60 |
| 30AQM8 | 925-1085 | | 727 | 31.8-38.8 | | 45.0 | 3.00 |
| 20ALH | 1210 | | 321 | 22.0 | | 40.0 | 2.20 |
| 25ALH | 1055 | | 491 | 29.0 | | 43.0 | 2.70 |
| 30KQT | 1185 | | 718 | 42.0 | | 46.0 | 4.90 |
| 40KQT | 1175 | | 1212 | 61.0 | | 49.0 | 6.40 |
| 50AEQ2 | 920 | | 2136 | 108.0 | | 54.0 | 11.50 |

* Specifications are subject to change without prior notice.
 ** Actual products & colours may vary from pictures shown.
 *** All KDK fans come with Thermal Safety Fuse.



KDK FANS (M) SDN BHD (Company No: 200201001186/568849-X)
 3rd Floor, 15 Jalan Tandang, 46050 Petaling Jaya, Selangor.
 Tel : 03-7785 5011
 Fax : 03-7785 2655
 Website: www.kdk.com.my

MP-20-A

SINCE 1909
 JAPAN



2020 | 2021
 1st Edition

